

AVIATION PCA DUCTING

The AVRODUCT™ product is designed and engineered to provide the best combination of quality, product uniformity, ease of installation, weight and thermal resistance.

- AVRODUCT™ uses a proprietary high-strength 19oz/yd² (644g/m²) exterior industrial grade fabric. This Tuff-coat fabric is flexible and resistant to environmental conditions.
- Materials and product assembly reduce weight without compromising quality or durability.
- This insulated product line is constructed using a three-ply PVC composition.
- AVRODUCT™ is available in Insulated and Non-insulated configurations.
- Our closed-cell foam insulation is sealed into a water-tight cavity and does not absorb or retain moisture from condensation. The insulation also includes a foil-faced surface which reduces temperature rise.
- Hi-strength welded construction provides exceptional airflow performance.
- A heavy-duty extruded wearstrip wraps around the duct body to reduce wear from dragging and handling.

SPECIFICATIONS	
STANDARD DIAMETERS	8", 12", 14" ID (203, 305, 356mm)
STANDARD LENGTH	20, 25 & 30' (6.1, 7.6 & 9.1m)
STANDARD COLOR	Yellow / Black
PITCH (SPIRAL WIRE)	4 – 6" (10 – 15cm)
TEMPERATURE RATING	-40 to 200°F (-40 to 93°C)
STANDARD END FINISH	HOOK&LOOP OR ZIPPER



AVRODUCT™ Layflat



AVRODUCT™ - Spiral Reinforced

END FINISH

HOOK & LOOP

6" (152mm) wide loop material on the air-inlet end and 6" wide hook material on the air-outlet end.



ZIPPER

Coil style zipper coupling protected with a fabric guard that fastens with hook & loop.

