

## INDUSTRIAL HEATER DUCTING

We offer a complete line of ducting products to meet your industrial heating requirements. Specialty fabrics are utilized to create products capable of delivering indirect-fired preheated air from ground heating equipment to various shelters and equipment.

Applications include industrial, commercial and residential work area heating, equipment heating, special events, drying, construction curing and more.



SPECIFICATIONS	
DIAMETER RANGE	6 – 36" ID (152 – 915mm)
STANDARD LENGTH	25' (7.6m)
STANDARD COLOR	Grey
PITCH	4" (10cm) - RETURN AIR 7" (18cm) - DISCHARGE/SUPPLY AIR
TEMPERATURE RATING	-65 to 500°F (-53 to 260°C)
FABRIC WEIGHT	17oz/yd <sup>2</sup> (576g/m <sup>2</sup> )

- Duct manufactured with our grey Silicone coated fiberglass fabric.
- Assembled using high-strength (lock-stitch) sewn construction, high tensile wire helix and extruded heavy duty wearstrip around the circumference for abrasion resistance. Comes with attached straps for storage and transporting.
- Product is well suited for extreme cold climates.
- Exceptional fire resistance properties.
- Standard end finish is a wire round end ring.
- Fabric material is flame resistant in accordance with the Canadian Standards Association Standard CAN/CSA-M427-M91 'Fire-Performance and Antistatic Requirements for Ventilation Materials.'

## END FINISH

### WIRE ROUND END RING

Wire ring encased in fabric interlocks one duct to another. This is our standard end finish.



### SOFT CUFF WITH STRAP (CLIP)

Smaller diameters use a 1" (25mm) steel clip buckle.



### SOFT CUFF

Folded fabric forms a 4" (102mm) finished cuff.



### SOFT CUFF WITH STRAP (CAM)

Larger diameters use a 1" (25mm) cam buckle.

