

INDUSTRIAL HVAC DUCTING

Manufactured with bi-directional airflow construction, reinforced with high tensile wire and enhanced with an abrasion resistant wearstrip around the circumference of the duct. Standard end finish includes our wire round end ring.

Applications include industrial and special event air conditioning, moderate heating, air-blowing and drying.



SPECIFICATIONS	
DIAMETER RANGE	8 - 36" (203 - 915mm)
STANDARD LENGTH	25' (7.6m)
STANDARD COLOR	Yellow / White
PITCH	4" (10cm) - RETURN AIR 7" (18cm) - DISCHARGE/SUPPLY AIR
TEMPERATURE RATING	-40 to 200°F (-40 to 93°C)
FABRIC WEIGHT	14oz/yd ² (475g/m ²)

- Quik-Kleen (QK) product line is manufactured using our industrial PVC reinforced polyester fabric with special **Urethane** topcoat.
- The Urethane topcoat forms a barrier that aids in preventing dirt from sticking to the fabric, allowing the duct to be easily cleaned.
- This duct is assembled using high-strength sewn construction and includes hanging tabs along the length.
- Construction can be varied to handle return air (negative pressure) and insulated requirements.
- Fabric conforms to the following fire resistant tests: NFPA 701-1999 Test 2 and California Administrative Code Title 19 (Paragraph 1237.1).

END FINISH

WIRE ROUND END RING

Wire ring encased in fabric interlocks one duct to another. This is our standard end finish.




SOFT CUFF WITH STRAP (CLIP)

Smaller diameters use a 1" (25mm) steel clip buckle.



SOFT CUFF

Folded fabric forms a 4" (102mm) finished cuff.



SOFT CUFF WITH STRAP (CAM)

Larger diameters use a 1" (25mm) cam buckle.

