

INDUSTRIAL HVAC DUCTING

Manufactured with high-strength sewn construction, reinforced with high tensile wire and enhanced with an abrasion resistant wearstrip around the circumference of the duct. Standard end finish includes our wire round end ring.

Applications include industrial and special event air conditioning, moderate heating, air-blowing and drying.



SPECIFICATIONS	
DIAMETER RANGE	8 - 36" (203 - 915mm)
STANDARD	25' (7.6m)
STANDARD COLOR	Yellow / White
PITCH	7" (18cm) - SUPPLY AIR
TEMPERATURE	-40 to 200°F (-40 to 93°C)
INSULATION COMPOSITION	3-PLY THERMAL BARRIER

- Quik-Kleen (QK-WI) insulated product line is constructed using a three-ply PVC insulated fabric composition with a special **Urethane** topcoat exterior.
- The Urethane topcoat forms a barrier that aids in preventing dirt from sticking to the fabric, allowing the duct to be easily cleaned.
- Insulation includes a layer of foil to help refract radiation from sunlight.
- Insulated composition helps to reduce overall heat gain and protects conditioned air over long lengths.
- This product line includes hanging tabs along the length.
- Fabric conforms to the following fire resistant tests: NFPA 701-1999 Test 2 and California Administrative Code Title 19 (Paragraph 1237.1).

END FINISH

WIRE ROUND END RING
Wire ring encased in fabric interlocks one duct to another. This is our standard end finish.



SOFT CUFF WITH STRAP (CLIP)
Smaller diameters use a 1" (25mm) steel clip buckle.



SOFT CUFF
Folded fabric forms a 4" (102mm) finished cuff.



SOFT CUFF WITH STRAP (CAM)
Larger diameters use a 1" (25mm) cam buckle.

